

Specification

LiftMaster

Rolling Door Opener

Model : LM950



Technical Data:

Electrical:	
Input voltage	220-240 Volt ~
Frequency	50/60 Hz
Power	110 W
Motor voltage	12 Volt
Rated load	40 Nm
Standby power	< 1 Watt
Plug type	3-Pin (UK)
Overload protection	yes
Temperature range	-30/+50°C
Application:	
Installation orientation	left or right side
Drive system	Direct drive
Pulling force @300mm dia drum	1300 N
Lighting System	LED (Ultra bright type)
Quantity of LEDs	12
Sun wheel material	Metal cast
Travel speed for 2.3m	~23 sec.
Sound peak value @1m	max. 59dBA
Side room requirement (minimum)*	45 mm
Extension poles for deep reach	yes (optional)
Max. drum rotations	4-1/2
Max. lifting height	5.500 mm
Rated door surface	25m ²
Max. door weight	250 kg
Control Board:	
Electronic travel distance limits	yes
Automatic operating force	yes
Automatic door close	yes
Door reversing for safety	yes
Accessory power output	yes
Diagnostic system	yes
Up/Down button on operator	yes
Automatic courtesy light delay	yes
IR-sensor connector	yes
Key switch / Push button connector	yes
Transmitter memory	64
Receiver frequency	433.30, 434.54 & 433.92MHz AM
Max. transmitter range (free field)	160 m
Other:	
Warranty period	2Y/5.000cycles :
Certifications	CE, SASO, KUSO, TUV-tested
Instructions with illustrations	yes
Instructions languages existing	EN, AR
Accessories (typically used):	
Wired push button with light	optional
Wireless push button	optional
Wireless keypad	optional
IR sensor	optional
Key switch	optional
Outside key switch	optional
Battery backup system	optional



The TX4UNIS universal receiver can be used with the new Evolution program as well as with any LiftMaster operator since 1997. The universal receiver has a white LED and operates on 433 MHz. It can replace all 433 MHz transmitters (TX4UNI, 94330E, 94333E, 94335E, 94334E as well as 4330E, 4333E, 4335E).



Wireless Keypad 747EV

for Garage Door Openers with EVO code

Open or close garage door without using a remote control or key. The LiftMaster Wireless Keyless Entry System can open the door using a private 4-digit code. Allows temporary access codes for visitors. Completely wireless, powered by one 9-volt battery (included). Weatherproof flip-up protective cover. Backlit keypad makes numbers easy to see, even in the dark.



Wireless Wall Control 128EV

for Evolution radio

2 channels, elegant design, easy to install, operates on 433 MHz



771EVK Failsafe infrared safety sensor

For use with all LiftMaster garage door openers

- Current draw: 20 mA max., IP44
- Incl. LED indicator, wall fittings and 2 x 10 m cable
- 2-wire system



E475M-12V

Battery back-up for LM950EVGBSA and LM850EVGBSA

- Battery status LED
- Easy plug in connection 12 V
- 80 cm cable